


TECHNICAL DRAWING OF A DETAIL C, SCALE 1:10, SHOWING SHORING ATTACHMENT OF UPPER BUNK TO FRAME AT STA # 55.

**DETAIL C**  
 SCALE 1:10  
 SHORING ATTACHMENT OF UPPER  
 BUNK TO FRAME AT STA # 55

**Dimensions and Specifications:**

- 28B1000-624 (REF)
- 3/4" x 3/4" x 3/4" AL
- ALLOY EXT. K78C
- SPEC 46AB COND T
- FINISH Z-P-2 AL
- AN300-9A
- AN360-D10
- AC 365-D1032
- (2 PLACES)
- AN442-04
- (3 PLACES)
- SKIN (REF)
- 28F3109-3 (REF)
- 0 1/2" x 3/8" x 2 1/2"
- AL ALLOY EXT ANGLE
- K 9876, SPEC 46AB CGN
- FINISH Z-P-2 AL
- 28B1000-626 (REF)
- 28F55 (REF)



1. INSTALLATION OF LOWER BUMPS  
AND SKIN AS FOR OTHER PORT-  
SIDE AND IS SHOWN ON  
28P4032 FOR PORT SIDE AND  
28P4032A FOR STD SIDE
2. UPPER AND LOWER  
BUMPS ARE PARALLEL & UPPER  
BUMP IS PARALLEL TO SKIN  
LINE
3. BEAM BEARING BRACKET FOR  
BEARING FIT WITH BUMP  
TUBE AFTER ASSY OF  
BEARINGS
4. FOR DETAIL OF ATTACHMENT  
NOT SHOWN ON THIS C/W  
SEE 28P4032.
5. -C ASSY IS FOR STD  
AND IS SHOWN & ASSY  
IS FOR PORT SIDE CF  
541P

[illegible]

PBY-5A # 2486, 2487 +  
# 2488 FOR MARINE  
AND ARE ALREADY  
COMPLETED.

H-366